

# **SAFETY DATA SHEET**

#### HARVEY CEMENT PRODUCTS, INC.

### Section 1: INDENTIFICATION

#### **1.1 PRODUCT IDENTIFIER:**

Product Name: CMU Block, Turlington<sup>®</sup> Brick, and SavannaStone<sup>®</sup> Cast Stone Product Code:

**1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE** Use: Construction material used in building and hardscape applications

#### **1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATE SHEET:**

Name/Address: Harvey Cement Products, Inc. 16030 Park Ave, Harvey, IL 60477

# 1.4EMERGENCY TELEPHONE NUMBEREmergency Number:CHEMTREC 1 (800) 424-9300Date of Preparation:November 27<sup>th</sup>, 2015Version#:1.1

#### Section 2: HAZARD(S) INDENTIFICATION

#### 2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

- Skin Irritation 2
- Eye Irritation 2A
- Skin Sensitization 1
- Carcinogenicity 1A
- Specific target organ toxicity Single Exposure 3
- Specific target organ toxicity Repeated Exposure 1

#### 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

Hazard Pictograms:



Signal Word:	Danger
Hazard Statement:	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Respirable dust may contain crystalline silica, known to cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.
PREVENTION:	Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well- ventilated area. Do not breathe dust.
RESPONSE:	If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in the eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
STORAGE:	Not applicable.
DISPOSAL:	Dispose of unused or unwanted concrete products in accordance with all local, regional, national and international regulations.

#### Harvey Cement Product's Inc.

CONFORMS TO OSHA HAZCOM 2012, CPR & NOM-018-STPS-2000 STANDARDS

Print Version 2016-01-27 Template Version 1.0

#### **2.3 ADDITIONAL INFORMATION**

Hazards not otherwise classified: Not applicable.

47% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### **3.1 MIXTURES**

Ingredient	UN#	H/F/R/*	CAS No	Wt. %
Aggregates	N/A	N/A	N/A	15-60
Portland cement	N/A	1/0/0	65997-15-1	10-30
Ashes [residues]	N/A	N/A	68131-74-8	0.1-30
Slags, ferrous metal, blast furnace	N/A	N/A	65996-69-2	0.1-30
Water	N/A	N/A	7732-18-5	10-30
Silica, crystalline, quartz	N/A	N/A	14808-60-7	3-7
Ferric oxide	UN1376	1/0/0	1309-37-1	1-5
Calcium carbonate	N/A	1/0/0	1317-65-3	1-5
Calcium hydroxide	N/A	3/0/0	1305-62-0	1-5
Silica, amorphous, fumed	N/A	N/A	7631-86-9	1-5
Admixtures [organic and inorganic]	N/A	N/A	N/A	0.1-1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of 1910.1200

\*Per NOM-018-STPS-2000

#### Section 4: FIRST AID MEASURES

#### 4.1 DESCRIPTION OF THE FIRST AID MEASURE

EYE: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If eye irritation persists: Get medical advice/attention.

	Print Version 2016-01-27 Template Version 1.0
SKIN:	If irritation occurs, flush skin with plenty of water. Remove contaminated
	clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

- INHALATION:If breathing is difficult, remove victim to fresh air and keep at rest in a position<br/>comfortable for breathing. Get medical advice/attention if you feel unwell.
- INGESTION: Not a normal route of exposure. May result in obstruction and temporary irritation of the digestive tract.

#### 4.3 INDICATIONS OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice immediately [show the label or SDS where possible]

#### Section 5: FIRE-FIGHTING MEASURES

#### 5.1 FLAMMABILITY

Flammability: Not flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.

#### 5.2 EXTINGUISHING MEDIA

Suitable Extinguishing Media: Treat for surrounding area.

Unsuitable Extinguishing Media: Not available.

#### 5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

#### 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear [full Bunker gear] and respiratory protection (SCBA).

#### Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING-UP

Methods of Containment:	Pick up large pieces, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for Cleaning-Up:	Vacuum or sweep material and place in a disposal container. Use wet methods, if appropriate, to reduce the generation of dust. Provide ventilation if dust is generated.

#### Section 7: HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

Handling:	Avoid contact with skin and eyes. Good housekeeping is important to		
	prevent accumulation of dust. Use wet methods, if appropriate, to		
	reduce the generation of dust. The use of compressed air for cleaning		
	clothing, equipment, etc. is not recommended. Handle with care. When		
	using do not eat or drink. (See Section 8)		

**GENERAL HYGEINE ADVICE:** Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

#### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage:

Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. (See section 10)

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **8.1 CONTROL PARAMETERS**

#### **Exposure Guidelines**

#### **OCCUPATIONAL EXPOSURE LIMITS**

Ingredient	OSHA-PEL	ACGIH-TLV
Coarse Aggregate	Not available.	Not available.
Portland cement	15 mg/m3 (total); 5 mg/m3 (resp)	1 mg/m3 (no asbestos and
		<1% crystalline silica,
		respirable fraction)
Ashes (residues)	Not available.	Not available.
Slags, ferrous metal, blast furnace	Not available.	Not available.
Water	Not available.	Not available.
Silica, Crystalline, Quartz	((10 mg/m3)/(%SiO2+2)(resp))	
	((30 mg/m3)/(%SiO2+2)(total))	
	((250)/(%SiOs+5) mppcf (resp))	0.025 mg/m3
Ferric oxide	10 mg/m3	5 mg/m3 (iron oxide
		fume;dust as Fe)
Calcium carbonate	15 mg/m3 (total); 5mg/m3 (resp)	10 mg/m3
Calcium hydroxide	15 mg/m3 (total); 5 mg/m3 (resp)	5 mg/m3
Silica, amorphous, fumed	80 mg/m3/%SiO2	10 mg/m3
Admixtures (organic and inorganic)	Not available.	Not available.

#### **8.2 EXPOSURE CONTROLS**

Engineering Controls: When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust.

#### **8.3 INDIVIDUAL PROTECTIVE MEASURES**

Personal Protective Equipment:

	Eye Face Protection:	Safety glasses or goggles are recommended when using product		
	Skin Protection:	Hand Protection: Wear suitable gloves.		
		Body Protection: Wear suitable protective clothing.		
Respira	atory Protection:	A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).		
Health	/Safety Measures	Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.		

#### Section 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Fully cured and hydrated concrete.
Color:	Not available.
Odor:	Odorless.
Odor Threshold:	Not available.
Physical State:	Solid.
рН:	Not available

Melting/Freezing Point:	Not available.
Initial Boiling Point/Range:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.
Flammability:	Not flammable.
Lower Flammability	Not available.
Upper Flammability	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density:	Not available.
Solubility:	Insoluble.
Partition coefficient:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.
Oxidizing Properties:	Not available.
Explosive Properties:	Not available.

#### Section 10: STABILITY AND REACTIVITY

**10.1 REACTIVITY** 

No dangerous reaction known under conditions of normal use.

**10.2 CHEMICAL STABILITY** 

Stable under normal conditions of use.

**10.3 POSSIBILITY OF HAZARDOUS REACTIONS** 

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

#### Harvey Cement Product's Inc. CONFORMS TO OSHA HAZCOM 2012, CPR & NOM-018-STPS-2000 STANDARDS Print Version 2016-01-27 Template Version 1.0

None known.

**10.5 INCOMPATIBLE MATERIALS** 

None known.

**10.6 HAZARDOUS DECOMPOSITION PRODUCTS** 

None known.

#### Section 11: TOXICOLOGICAL INFORMATION

#### **11.1 INFORMATION ON TOXICOLOGICAL EFFECTS**

Likely Routes of Exposure: Skin contact, eye contact, and inhalation.

Symptoms related to physical/chemical/toxicological characteristics:

Eye:	Causes serious eye irritation. Symptoms may include discomfort or pain, excess
	blinking and tear production, with possible redness and swelling.

- Skin: Causes skin irritation. Wear gloves when handling product to avoid drying and mechanical abrasion of the skin. May cause sensitization by skin contact.
- Ingestion: Not a normal route of exposure. May result in obstruction and temporary irritation of the digestive tract.

Inhalation: Dust may cause respiratory tract irritation.

Acute Toxicity:

Ingredient	IDLH	LC50	LD50
Coarse aggregate	Not available	Not available	Not available
Portland cement	5000 mg/m3	Not available	Not available
Ashes (residues)	Not available.	Not available	Oral > 2000 mg/kg, rat
Slags, ferrous metal	Not available.	Not available	Not available
Water	Not available.	Inhalation 90000 mg/m3/4h, rat	Oral >90000 mg/kg, rat Dermal>90000 mg/kg, rabbit
Silica, crystalline, quartz	Ca [25 mg/m3 (cristobalite, tridymite); 50 mg/m3 (quartz, tripoli	Not available	Oral 500 mg/kg, rat
Ferric oxide	2500 mg Fe/m3	Not available	Oral>10000 mg/kg, rat
Calcium carbonate	Not available	Not available	Oral 6450 mg/kg, rat

Page 9 | 15

#### Harvey Cement Product's Inc. CONFORMS TO OSHA HAZCOM 2012, CPR & NOM-018-STPS-2000 STANDARDS Print Version 2016-01-27 Template Version 1.0

Calcium hydroxide	Not available	Not available	Oral 7340 mg/kg, rat
Silica, amorphous, fumed	Not available	Inhalation >58.8 mg/l/1h, rat	Oral>5000 mg/kg, rat Dermal>2000 mg/kg, rabbit
Admixtures (organic/inorganic)	Not available	Not available	Not available

#### **Calculated Overall Chemical Acute Toxicity Values**

LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
>5 mg/l/4h, rat	>2000 mg/kg, rat	>2000 mg/kg, rabbit

Ingredient	Chemical Listed as Carcinogen or Potential
	Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Coarse Aggregate	Not listed.
Portland Cement	G-A4
Ashes (residues)	Not listed
Slags, ferrous metal, blast furnace	Not listed
Water	Not listed
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65
Ferric oxide	G-A4, I-3
Calcium carbonate	Not listed
Calcium hydroxide	Not listed
Silica, amorphous, fumed	I-3
Admixtures (organic and inorganic)	Not listed

\*See Section 15 for more information

#### 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT-AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation:	Causes skin irritation
Serious Eye Damage/Irritation:	Causes serious eye irritation
Respiratory Sensitization:	Based on available data, the classification criteria are not met.
Skin Sensitization:	May cause an allergic skin reaction.
STOT-Single Exposure:	Dust may cause respiratory tract irritation.
Chronic Health Effects:	Not available.
Carcinogenicity:	Respirable dust may contain crystalline silica, known to cause cancer.
Germ Cell Mutagenicity:	Based on available data, the classification criteria are not met.
Reproductive Toxicity:	Not available.
Developmental:	Based on available data, the classification criteria are not met.
Teratogenicity:	Based on available data, the classification criteria are not met.

#### Harvey Cement Product's Inc.

#### CONFORMS TO OSHA HAZCOM 2012, CPR & NOM-018-STPS-2000 STANDARDS

Embryotoxicity:	Print Version 2016-01-27 Template Version 1.0 Based on available data, the classification criteria are not met.
Fertility:	Based on available data, the classification criteria are not met.
STOT-Repeated Exposure:	Causes damage to lungs through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed in the International Agency for Research on Cancer (IARC) and National Toxicity Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
Aspiration Hazard:	Based on the available data, the classification criteria are not met.
Toxic Synergistic Materials:	Not available.
Other Information:	Not available.

#### Section 12: ECOLOGICAL INFORMATION

#### **12.1 ECOTOXITY**

Acute/Chronic Toxicity: No ecological consideration when used according to directions.

#### **12.2 PERSISTENCE AND DEGRADABILITY**

Not available.

#### **12.3 BIOACCUMULATIVE POTENTIAL**

Bioaccumulation: Not available.

#### **12.4 MOBILITY IN SOIL**

Not available.

#### **12.5 OTHER ADVERSE EFFECTS**

These products are generally considered chemically inert in the environment.

#### **ENVIRONMENTAL EFFECT ON AQUATIC HABITAT:**

Uncured cementitious materials or finely divided (crushed) concrete material is an environmental hazard, which may adversely affect fish and other wildlife. Do not use crushed concrete as fill near any aquatic habitat. Discharge of large quantities to any waterways would be expected to cause significant consequence on aquatic habitat.

#### Section 13: DISPOSAL CONSIDERATIONS

#### **13.1 WASTE TREATMENT METHODS**

**Disposal Method:** 

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Other disposal recommendations:

Not available.

#### Section 14: TRANSPORT INFORMATION

14.1 UN NUMBER		
DOT	TDG	NOM-004-SCT2-1994
Not regulated	Not regulated	Not regulated
14.2 UN PROPER SHIPPING NAME		
DOT	TDG	NOM-004-SCT2-1994
Not applicable	Not applicable	Not applicable
14.3 TRANSPORT HAZARD CLASS (ES)		
DOT	TDG	NOM-004-SCT2-1994
Not applicable	Not applicable	Not applicable
14.4 PACKING GROUP		
DOT	TDG	NOM-004-SCT2-1994
Not applicable	Not applicable	Not applicable
14.5 ENVIRONMENTAL HAZARDS		

Print Version 2016-01-27 Template Version 1.0

Not available.

#### 14.6 TRASNPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

**14.7 SPECIAL PRECAUTIONS FOR USER** 

Do not handle until all safety precautions have been read and understood.

#### Section 15: REGULATORY INFORMATION

## 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

US: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200 HazCom 2012)

#### Ingredient Section 302 Section 304 CERCLA Section 313 (EHS) TPQ (lbs) EHS RQ (lbs) RQ (lbs) Not listed. **Coarse aggregate** Not listed. Not listed. Not listed. Not listed. Portland cement Not listed. Not listed. Not listed. Not listed. Ashes (residues) Not listed. Not listed. Not listed. Slags, ferrous metal, blast Not listed. Not listed. Not listed. Not listed. furnace Not listed. Water Not listed. Not listed. Not listed. Silica, crystalline, quartz Not listed. Not listed. Not listed. Not listed. Ferric oxide Not listed. Not listed. Not listed. Not listed. **Calcium carbonate** Not listed. Not listed. Not listed. Not listed. Not listed. Calcium hydroxide Not listed. Not listed. Not listed. Silica, amorphous, fumed Not listed. Not listed. Not listed. Not listed. **Admixtures** Not listed. Not listed. Not listed. Not listed. (organic/inorganic)

#### SARA TITLE III

**State Regulations** 

California Proposition 65 Warning:

Dry cutting, sanding or grinding of concrete products will expose you to respirable crystalline silica which is "known in the State of California to cause cancer and to contain other substances which are known to the State of California to cause cancer, birth defects and other reproductive harm."

**Global Inventories:** 

Ingredient	Canada DSL/NDSL	USA TSCA
Coarse aggregate	Not available.	Not available.
Portland cement	DSL	Yes.
Ashes (residues)	DSL	Yes.

Print Version 2016-01-27 Template Version 1.0

Slags, ferrous metal, furnace	DSL	Yes.
Water	DSL	Yes.
Silica, crystalline, quartz	DSL	Yes.
Ferric oxide	DSL	Yes.
Calcium carbonate	NDSL	Yes.
Calcium hydroxide	DSL	Yes.
Silica, amorphous, fumed	DSL	Yes.
Admixtures (organic/inorganic)	Not available.	Not available.

#### **NFPA-National Fire Protection Association**

Health:	2
Fire:	0
Reactivity:	0

#### **HMIS-Hazardous Materials Identification System:**

Health:	2*
Fire:	0
Physical Hazard:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

#### SOURCE AGENCY CARCINOGEN CLASSICATIONS

**CP65 California Proposition 65** 

#### OSHA(O) Occupational Safety and Health Administration

ACGIH G) American Conference of Governmental Industrial Hygienists

- A1 Confirmed human carcinogen •
- A2 Suspected human carcinogen
- A3 Animal carcinogen •
- A4 Not classifiable as a human carcinogen
- A5 Not suspected as a human carcinogen

#### IARC (I)

- International Agency for Research on Cancer
- 1. The agent (mixture) is carcinogenic to humans.
- 2. A. The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

B. The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

- 3. The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4. The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

#### NTP(N) National Toxicology Program

- 1. Known to be carcinogens
- 2. Reasonably anticipated to be carcinogens.

#### Section 16: OTHER INFORMATION

Date of preparation:	January 27, 2016
Expiry Date:	January 27, 2019
Version:	1
<b>Revision Dates:</b>	N/A

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

## **END OF SAFETY DATA SHEET**

### Harvey Cement Products, Inc. 16030 Park Ave. Harvey, IL 60426 PH: 708-333-1900 FX: 708-333-1910 www.harveycement.com